## Product/Chemical #: Fiberglass Reinforced Polymer (FRP) 1525 Special Resin Series

Date of Preparation: 3/28/2016

CREATIVE

COMPOSITES

GROUP

Creative Pultrusions, Inc 214 Industrial Lane Alum Bank, PA 15521 814-839-4186 CreativeCompositesGroup.com

## Safety Data Sheet

## Product/Chemical #: Fiberglass Reinforced Polymer (FRP) 1525 Special Resin Series

Date of Preparation: 3/28/2016

## Section 1 – Materials and Company Identification

Product/Chemical Name: Fire Retardant Thermoset Polyester Fiberglass Reinforced Composite

Trade Name: Pultex® 1525 Special General Use: Structural Component

Manufacturer: Creative Pultrusions, Inc., 214 Industrial Lane, Alum Bank, PA 15521-8304

PHONE (814) 839-4186, FAX (814) 839-4276 (8:00AM – 4:30PM EST)

24 Hour Emergency Phone Number: (814) 839-4186

#### Section 2 – Hazards Identification

GHS-US Classification: As manufactured this product is considered non-hazardous according to GHS.

Label Elements: None required

Other Hazard(s): Product will form dust and particulate matter when drilling, grinding, cutting or sanding.

Dust is combustible.

**Acute Effects** 

**Inhalation:** Fibrous glass dust from machining can cause irritation. **Eye:** Fibrous glass dust from machining can cause irritation. **Skin:** Fibrous glass dust from machining can cause irritation.

Ingestion: N/A Carcinogenicity: N/A

Medical Conditions Aggravated by Long-Term Exposure: N/A

#### Section 3 – Material Composition and Information on Ingredients

Ingredient NameCAS NumberPercent by WeightPolymerized Polyester Resin MixtureNone25%-55%Fiberglass659997-17-345%-75%

#### **Section 4 – First Aid Measures**

Inhalation: Remove from dust to fresh air.

Eye Contact: Flush with water or eye rinse.

Skin Contact: Wash with soap and cold water.

**Ingestion:** N/A

If condition persists, get appropriate in-plant medical support or consult physician.

## Product/Chemical #: Fiberglass Reinforced Polymer (FRP) 1525 Special Resin Series

Date of Preparation: 3/28/2016

## Section 5 – Fire Fighting Measures

**Flash Point:** 675°F / 357.2°C (dust)

Extinguishing Media: Water, Foam, Type A, B, or C extinguishers

**Unusual Fire or Explosion Hazards:** Do not expose fine dust to an ignition source.

Hazardous Combustion Products: Heavy Smoke, CO, CO<sub>2</sub>, and irritating or toxic vapors and gases

**Fire-Fighting Instructions:** Use self-contained breathing apparatus

#### **Section 6 – Accidental Release Measures**

The product as manufactured is non-hazardous. In areas where drilling, grinding, cutting or sanding occurs on this product, care should be taken to clean up dust. Dust deposits should not be allowed to accumulate on surfaces. Dust is considered a St 1 class dust with a Kst (bar-m/s) of less than 100. Avoid dispersal of dust with compressed air.

## Section 7 – Handling and Storage

Minimize dust generation and accumulation through routine housekeeping to ensure that dusts do not accumulate on surfaces.

Protective gloves are recommended for handling material comfortably. Long sleeved shirts and pants minimize exposure to nuisance dust.

## **Section 8 – Exposure Controls/Personal Protection**

Component	CAS	Percent	ACGIH	OSHA	Units
			TLV	PEL	
Polymerized Polyester Resin	None	25%-55%	Not	Not	Not
Mixture			Established	Established	Established
Fiberglass	659997-17-3	45%-75%	Not	Not	Not
			Established	Established	Established
Fibrous Glass Dust	None	N/A	5	15 (total)	mg/m <sup>3</sup>

**Engineering Controls / Ventilation:** Must comply with NFPA 68

Respiratory Protection: None required if dust is not present. When dust exposures have the potential to

exceed regulated values, a NIOSH approved dust mask must be used.

Eye Protection: Safety glasses with side shields or goggles.

**General:** Safety Glasses, Gloves, long sleeved shirts and pants recommended.

#### Section 9 – Physical and Chemical Characteristics

**Appearance:** Various colors and shapes

structural profiles

**Odor:** No significant odor

pH: N/A

Melting Point/Freezing Point: N/D

**Initial Boiling Point: N/A** 

Flash Point: N/A **Evaporation Rate: N/A** 

Flammability: N/D

**Upper/Lower Explosion Limit:** N/A

Vapor Pressure: N/A Vapor Density: N/A Specific Gravity: 1.61-2.0

Solubility: N/A

Partition Coefficient: N/A **Auto-Ignition Temperature:** N/D **Decomposition Temperature:** N/D

Viscosity: N/A

## Product/Chemical #: Fiberglass Reinforced Polymer (FRP) 1525 Special Resin Series

Date of Preparation: 3/28/2016

#### Section 10 – Stability/Reactivity

**Stability:** Product is stable.

Polymerization: Hazardous polymerization will not occur.

**Conditions to avoid:** Extreme heat, sources of ignition and flames. **Incompatibilities:** Do not store with strong oxidizing agents.

Hazardous decomposition products: Heavy Smoke, CO, CO2, and irritating or toxic vapors and gases.

### **Section 11 – Toxicological Information**

No toxicological test data is available for this product.

#### **Section 12 – Ecological Information**

No ecotoxicity test data is available for this product. This product is not expected to present a hazard to aquatic and terrestrial environments.

## Section 13 – Disposal Considerations

As supplied this product is non-hazardous. Consult federal, state and local regulations for proper disposal.

## **Section 14 – Transport Information**

## **DOT Transportation Data (49 CFR 172.101):**

Shipping Name: Not Regulated Packing Group: Not Determined

Shipping Symbols: N/A Label: Not Required

Hazard Class: Not Hazardous Special Provisions (172.102): None

ID No.: N/A

## **Section 15 – Regulatory Information**

**TSCA Inventory:** All ingredients are on the TSCA inventory.

**SARA Section 313:** None above de minimus quantity.

SARA 311/312: None as supplied.

OSHA Hazardous Communication Categories: Dust is combustible and an irritant.

Canada-WHMIS Classification: Non-hazardous

California Proposition 65: WARNING: This product can expose you to chemicals including styrene, which is known to the State of California to cause cancer. For more information go to www.P65Warnings.ca.gov.

#### **Section 16 – Other Information**

Refer to NFPA 654, standard for the prevention of fire and dust explosion from the manufacturing, processing and handling of combustible particulate solids, for safe handling of dusts generated during processing.

N/D - Not Determined N/A - Not Applicable

Prepared By: Ronald W. Allison

Last Revision: 11.08.22

Page 3 of 4 CPQ106-0712 Rev. 11.08.22

# Product/Chemical #: Fiberglass Reinforced Polymer (FRP) 1525 Special Resin Series

Date of Preparation: 3/28/2016

**Disclaimer:** While the information and recommendations set forth in the SDS are believed to be accurate as of the date of the SDS preparation, Creative Pultrusions, Inc. makes no representation or warranty, direct or indirect, regarding their accuracy or completeness nor do we assume any obligations to advise you of any modifications or corrections to or of such information and recommendations of which we may become aware from the date hereof. Recipients are advised to confirm as they may deem acceptable that the information and recommendations are current and applicable to meet their requirements. Since the conditions are methods of use of this product are beyond our control, Creative Pultrusions, Inc. disclaims any and all liability arising out of the use of this product or the information provided herewith.