

## Ladder Cable Tray - Weights, Lbs / Ft

| Tray Width | Rung Spacing | ELL3 | EHL4 | ETL4 | ELL6 | ETL6 | EHZ6 | EHL6 | D-EHL6 | EHL8 | D-EHL10 |
|------------|--------------|------|------|------|------|------|------|------|--------|------|---------|
| 6"         | 6"           | 2.1  | 3.1  | 3.1  | 4.6  | 3.0  | 4.9  | 4.6  | 5.0    | 6.5  | 9.6     |
|            | 9.25"        | 1.9  | 2.9  | 2.9  | 4.3  | 2.7  | 4.7  | 4.3  | 4.8    | 6.2  | 9.3     |
|            | 12"          | 1.8  | 2.8  | 2.8  | 4.2  | 2.6  | 4.6  | 4.2  | 4.7    | 6.1  | 9.2     |
|            | 18.5"        | 1.7  | 2.7  | 2.7  | 4.1  | 2.5  | 4.4  | 4.1  | 4.6    | 6.0  | 9.1     |
| 9"         | 6"           | 2.3  | 3.4  | 3.4  | 4.8  | 3.2  | 5.1  | 4.8  | 5.3    | 6.7  | 9.8     |
|            | 9.25"        | 2.0  | 3.0  | 3.0  | 4.5  | 2.9  | 4.8  | 4.5  | 5.0    | 6.4  | 9.5     |
|            | 12"          | 1.9  | 2.9  | 2.9  | 4.4  | 2.8  | 4.7  | 4.4  | 4.8    | 6.3  | 9.3     |
|            | 18.5"        | 1.7  | 2.7  | 2.7  | 4.2  | 2.6  | 4.5  | 4.2  | 4.7    | 6.1  | 9.2     |
| 12"        | 6"           | 2.6  | 3.6  | 3.6  | 5.0  | 3.4  | 5.4  | 5.0  | 5.5    | 6.9  | 10.0    |
|            | 9.25"        | 2.2  | 3.2  | 3.2  | 4.6  | 3.0  | 5.0  | 4.6  | 5.1    | 6.5  | 9.6     |
|            | 12"          | 2.0  | 3.0  | 3.0  | 4.5  | 2.9  | 4.8  | 4.5  | 4.9    | 6.4  | 9.4     |
|            | 18.5"        | 1.8  | 2.8  | 2.8  | 4.3  | 2.7  | 4.6  | 4.3  | 4.7    | 6.2  | 9.2     |
| 18"        | 6"           | 3.1  | 4.1  | 4.1  | 5.5  | 3.9  | 5.8  | 5.5  | 6.0    | 7.4  | 10.5    |
|            | 9.25"        | 2.5  | 3.5  | 3.5  | 5.0  | 3.3  | 5.3  | 5.0  | 5.4    | 6.9  | 9.9     |
|            | 12"          | 2.2  | 3.3  | 3.3  | 4.7  | 3.1  | 5.0  | 4.7  | 5.2    | 6.6  | 9.7     |
|            | 18.5"        | 2.0  | 3.0  | 3.0  | 4.4  | 2.8  | 4.7  | 4.4  | 4.9    | 6.3  | 9.4     |
| 24"        | 6"           | 3.5  | 4.5  | 4.5  | 6.0  | 4.4  | 6.3  | 6.0  | 6.4    | 7.9  | 11.0    |
|            | 9.25"        | 2.8  | 3.8  | 3.8  | 5.3  | 3.6  | 5.6  | 5.3  | 5.7    | 7.2  | 10.2    |
|            | 12"          | 2.5  | 3.5  | 3.5  | 4.9  | 3.3  | 5.3  | 4.9  | 5.4    | 6.8  | -       |
|            | 18.5"        | 2.1  | 3.1  | 3.1  | 4.6  | 3.0  | 4.9  | 4.6  | 5.0    | 6.5  | -       |
| 30"        | 6"           | 4.0  | 5.0  | 5.0  | 6.5  | 4.8  | 6.8  | 6.5  | 6.9    | 8.4  | -       |
|            | 9.25"        | 3.1  | 4.1  | 4.1  | 5.6  | 4.0  | 5.9  | 5.6  | 6.0    | 7.5  | -       |
|            | 12"          | 2.7  | 3.7  | 3.7  | 5.2  | 3.6  | 5.5  | 5.2  | 5.6    | 7.1  | -       |
| 36"        | 6"           | 4.5  | 5.5  | 5.5  | 6.9  | 5.3  | 7.2  | 6.9  | 7.4    | 8.8  | -       |
|            | 9.25"        | 3.4  | 4.4  | 4.4  | 5.9  | 4.3  | 6.2  | 5.9  | 6.3    | 7.8  | -       |
|            | 12"          | 2.9  | 4.0  | 4.0  | 5.4  | 3.8  | 5.7  | 5.4  | 5.9    | 7.3  | -       |

Values are applicable to all resin systems, where possible.