



Note: Dimensional tolerances per ASTM D3917

<table border="1"> <thead> <tr> <th colspan="3">Imperial Units</th> <th colspan="3">Metric Units</th> </tr> <tr> <th colspan="3">Cross Section Properties</th> <th colspan="3">Cross Section Properties</th> </tr> </thead> <tbody> <tr> <td>Area</td><td>1.918</td><td>in<sup>2</sup></td> <td>Area</td><td>1.237E+03</td><td>mm<sup>2</sup></td> </tr> <tr> <td>Ix</td><td>4.530</td><td>in<sup>4</sup></td> <td>Ix</td><td>1.886E+06</td><td>mm<sup>4</sup></td> </tr> <tr> <td>Iy</td><td>.329</td><td>in<sup>4</sup></td> <td>Iy</td><td>1.369E+05</td><td>mm<sup>4</sup></td> </tr> <tr> <td>Ixy</td><td>0</td><td>in<sup>4</sup></td> <td>Ixy</td><td>0</td><td>mm<sup>4</sup></td> </tr> <tr> <td>Sx</td><td>2.265</td><td>in<sup>3</sup></td> <td>Sx</td><td>3.712E+04</td><td>mm<sup>3</sup></td> </tr> <tr> <td>Sy</td><td>.329</td><td>in<sup>3</sup></td> <td>Sy</td><td>5.391E+03</td><td>mm<sup>3</sup></td> </tr> <tr> <td>rx</td><td>1.537</td><td>in</td> <td>rx</td><td>3.904E+01</td><td>mm</td> </tr> <tr> <td>ry</td><td>.414</td><td>in</td> <td>ry</td><td>1.052E+01</td><td>mm</td> </tr> </tbody> </table>			Imperial Units			Metric Units			Cross Section Properties			Cross Section Properties			Area	1.918	in <sup>2</sup>	Area	1.237E+03	mm <sup>2</sup>	Ix	4.530	in <sup>4</sup>	Ix	1.886E+06	mm <sup>4</sup>	Iy	.329	in <sup>4</sup>	Iy	1.369E+05	mm <sup>4</sup>	Ixy	0	in <sup>4</sup>	Ixy	0	mm <sup>4</sup>	Sx	2.265	in <sup>3</sup>	Sx	3.712E+04	mm <sup>3</sup>	Sy	.329	in <sup>3</sup>	Sy	5.391E+03	mm <sup>3</sup>	rx	1.537	in	rx	3.904E+01	mm	ry	.414	in	ry	1.052E+01	mm		Part Description:	
			Imperial Units			Metric Units																																																											
Cross Section Properties			Cross Section Properties																																																														
Area	1.918	in <sup>2</sup>	Area	1.237E+03	mm <sup>2</sup>																																																												
Ix	4.530	in <sup>4</sup>	Ix	1.886E+06	mm <sup>4</sup>																																																												
Iy	.329	in <sup>4</sup>	Iy	1.369E+05	mm <sup>4</sup>																																																												
Ixy	0	in <sup>4</sup>	Ixy	0	mm <sup>4</sup>																																																												
Sx	2.265	in <sup>3</sup>	Sx	3.712E+04	mm <sup>3</sup>																																																												
Sy	.329	in <sup>3</sup>	Sy	5.391E+03	mm <sup>3</sup>																																																												
rx	1.537	in	rx	3.904E+01	mm																																																												
ry	.414	in	ry	1.052E+01	mm																																																												
4" x 2" x 1/4" I-Beam		Part Number:																																																															
Pultex® IB440		Units:	Scale:																																																														
Imperial/Metric		Full																																																															
All information herein for reference only																																																																	

CREATIVE PULTRUSIONS INC.  
 214 Industrial Lane  
 Alum Bank, Pennsylvania 15521  
 www.creativepultrusions.com  
 (814) 839-4186 (888) CPI-PULL