


Note: Dimensional tolerances per ASTM D3917

Imperial Units			Metric Units		
Cross Section Properties			Cross Section Properties		
Area	.899	in <sup>2</sup>	Area	5.800E+02	mm <sup>2</sup>
I <sub>x</sub>	.036	in <sup>4</sup>	I <sub>x</sub>	1.498E+04	mm <sup>4</sup>
I <sub>y</sub>	2.366	in <sup>4</sup>	I <sub>y</sub>	9.848E+05	mm <sup>4</sup>
I <sub>xy</sub>	0	in <sup>4</sup>	I <sub>xy</sub>	0	mm <sup>4</sup>
S <sub>x</sub>	.108	in <sup>3</sup>	S <sub>x</sub>	1.770E+03	mm <sup>3</sup>
S <sub>y</sub>	.800	in <sup>3</sup>	S <sub>y</sub>	1.311E+04	mm <sup>3</sup>
r <sub>x</sub>	.201	in	r <sub>x</sub>	5.105E+00	mm
r <sub>y</sub>	1.623	in	r <sub>y</sub>	4.122E+01	mm

 <b>CREATIVE PULTRUSIONS</b>			<b>Part Description:</b> 6" x 1/2" x 1/8" Toe Plate	
CREATIVE PULTRUSIONS INC. 214 Industrial Lane Alum Bank, Pennsylvania 15521 www.creativepultrusions.com (814) 839-4186			<b>Part Number:</b> PulTex® SS800	
<b>Units:</b> Imperial/Metric		<b>Scale:</b> Full		
All information herein for reference only				