


Note: Dimensional tolerances per ASTM D3917

Imperial Units			Metric Units		
Cross Section Properties			Cross Section Properties		
Area	6.168	in <sup>2</sup>	Area	3.980E+03	mm <sup>2</sup>
I <sub>x</sub>	36.191	in <sup>4</sup>	I <sub>x</sub>	1.506E+07	mm <sup>4</sup>
I <sub>y</sub>	197.960	in <sup>4</sup>	I <sub>y</sub>	8.240E+07	mm <sup>4</sup>
I <sub>xy</sub>	33.361	in <sup>4</sup>	I <sub>xy</sub>	1.389E+07	mm <sup>4</sup>
S <sub>x</sub>	12.028	in <sup>3</sup>	S <sub>x</sub>	1.971E+05	mm <sup>3</sup>
S <sub>y</sub>	18.649	in <sup>3</sup>	S <sub>y</sub>	3.056E+05	mm <sup>3</sup>
r <sub>x</sub>	2.422	in	r <sub>x</sub>	6.152E+01	mm
r <sub>y</sub>	5.665	in	r <sub>y</sub>	1.439E+02	mm

 <p>CREATIVE PULTRUSIONS INC. 214 Industrial Lane Alum Bank, Pennsylvania 15521 www.creativepultrusions.com (814) 839-4186</p>		Part Description:	
		SuperLoc® Series 1560	
Part Number:		SS806	
Units:	Imperial/Metric	Scale:	Full
All information herein for reference only			