



Note: Dimensional tolerances per ASTM D3917

Imperial Units			Metric Units		
Cross Section Properties			Cross Section Properties		
Area	3.018	in <sup>2</sup>	Area	1.947E+03	mm <sup>2</sup>
I <sub>x</sub>	2.151	in <sup>4</sup>	I <sub>x</sub>	8.953E+05	mm <sup>4</sup>
I <sub>y</sub>	1.294	in <sup>4</sup>	I <sub>y</sub>	5.386E+05	mm <sup>4</sup>
I <sub>xy</sub>	.152	in <sup>4</sup>	I <sub>xy</sub>	6.327E+04	mm <sup>4</sup>
S <sub>x</sub>	1.283	in <sup>3</sup>	S <sub>x</sub>	2.102E+04	mm <sup>3</sup>
S <sub>y</sub>	.866	in <sup>3</sup>	S <sub>y</sub>	1.419E+04	mm <sup>3</sup>
r <sub>x</sub>	.844	in	r <sub>x</sub>	2.144E+01	mm
r <sub>y</sub>	.655	in	r <sub>y</sub>	1.664E+01	mm



CREATIVE PULTRUSIONS INC.  
 214 Industrial Lane  
 Alum Bank, Pennsylvania 15521  
 www.creativepultrusions.com  
 (814) 839-4186 (888) CPI-PULL

Part Description:

SuperLoc® Series 1610 Connector

Part Number:

SS821

Units:

Imperial/Metric

Scale:

Full

All information herein for reference only