Date of Preparation: 2/16/2016



Creative Pultrusions, Inc 214 Industrial Lane Alum Bank, PA 15521 814-839-4186 CreativeCompositesGroup.com

Safety Data Sheet

Product/Chemical #: Pultruded Fiberglass Grating with Anti-Slip Surface

Date of Preparation: 2/16/2016

Section 1 – Materials and Company Identification

Product/Chemical Name: Fiberglass Reinforced Thermoset Polymerized Resin Composite with

Crystalline Silica Sand(quartz) Anti-Slip Surface

Trade Name: Supergrate®

General Use: Structural Component

Manufacturer: Creative Pultrusions, Inc., 214 Industrial Lane, Alum Bank, PA 15521-8304

PHONE (814) 839-4186, FAX (814) 839-4276 (8:00AM – 4:30PM EST)

24 Hour Emergency Phone Number: (814) 839-4186

Section 2 - Hazards Identification

GHS-US Classification: As manufactured this product is considered non-hazardous according to GHS.

Label Elements: None required

Other Hazard(s): Product will form dust and particulate matter when drilling, grinding, cutting or sanding. Dust is combustible. Any dust containing silica sand is considered hazardous under the OSHA Hazardous Communication Standard

Acute Effects

Inhalation: Fibrous glass dust from machining can cause irritation.

Eye: Fibrous glass dust from machining can cause irritation. **Skin:** Fibrous glass dust from machining can cause irritation.

Ingestion: N/A Chronic Effects

Inhalation: The prolonged and repeated inhalation of respirable crystalline silica can cause silicosis.

Carcinogenicity: Respirable crystalline silica is classified as carcinogenic to humans Medical Conditions Aggravated by Long-Term Exposure: None as manufactured.

Section 3 – Material Composition and Information on Ingredients

<u>Ingredient Name</u>	CAS Number	Percent by Weight	
Polymerized Resin Mixture	None	25%-45%	
Fiberglass	659997-17-3	55%-75%	
Crystalline Silica (quartz)	14808-60-7	0% - 4%	

Date of Preparation: 2/16/2016

Section 4 – First Aid Measures

Inhalation: Remove from dust to fresh air.

Eye Contact: Flush with water or eye rinse.

Skin Contact: Wash with soap and cold water.

Ingestion: N/A

If condition persists, get appropriate in-plant medical support or consult physician.

Section 5 – Fire Fighting Measures

Flash Point: 675°F / 357.2°C (dust)

Extinguishing Media: Water, Foam, Type A, B, or C extinguishers

Unusual Fire or Explosion Hazards: Do not expose fine dust to an ignition source.

Hazardous Combustion Products: Heavy Smoke, CO, CO2, and irritating or toxic vapors and gases

Fire-Fighting Instructions: Use self-contained breathing apparatus

Section 6 – Accidental Release Measures

The product as manufactured is non-hazardous. In areas where drilling, grinding, cutting or sanding occurs on this product, care should be taken to clean up dust. Dust deposits should not be allowed to accumulate on surfaces. Dust is considered a St 1 class dust with a Kst (bar-m/s) of less than 100. Avoid dispersal of dust with compressed air.

Section 7 – Handling and Storage

Minimize dust generation and accumulation through routine housekeeping to ensure that dusts do not accumulate on surfaces. Keep airborne dust concentrations below permissible exposure limits.

Protective gloves are recommended for handling material comfortably. Long sleeved shirts and pants minimize exposure to dust.

Section 8 - Exposure Controls/Personal Protection

Component	CAS	Percent	ACGIH	OSHA	Units
			TLV	PEL	
Polymerized Polyester Resin	None	25%-55%	Not	Not	Not
Mixture			Established	Established	Established
Fiberglass	659997-17-3	45%-75%	Not	Not	Not
_			Established	Established	Established
Fibrous Glass Dust	None	N/A	5	15 (total)	mg/m ³
Crystalline Silica (quartz)	140808-60-7	0%-4%	.025 (resp.)	10 (%	mg/m ³
				$SiO_2+2)$	

Engineering Controls / Ventilation: Must comply with NFPA 68

Respiratory Protection: None required if dust is not present. Keep airborne dust concentrations below permissible exposure limits. When dust exposures have the potential to exceed regulated values, a NIOSH approved dust mask must be used.

Eve Protection: Safety glasses with side shields or goggles.

General: Safety Glasses, Gloves, long sleeved shirts and pants recommended.

Page 2 of 4 CPQ112-0712 Rev. 11.08.22

Date of Preparation: 2/16/2016

Section 9 – Physical and Chemical Characteristics

Appearance: Various colors and shapes Upper/Lower Explosion Limit: N/A

structural profiles

Odor: No significant odor Vapor Density: N/A pH: N/A Specific Gravity: 1.61-2.0

pii. N/A

Melting Point/Freezing Point: N/D

Initial Boiling Point: N/A

Flash Point: N/A Evaporation Rate: N/A Flammability: N/D Partition Coefficient: N/A

Vapor Pressure: N/A

Auto-Ignition Temperature: N/D **Decomposition Temperature:** N/D

Viscosity: N/A

Solubility: N/A

Section 10 – Stability/Reactivity

Stability: Product is stable.

Polymerization: Hazardous polymerization will not occur.

Conditions to avoid: Extreme heat, sources of ignition and flames.

Incompatibilities: Do not store with strong oxidizing agents. Do not expose crystalline silica to

hydrofluoric acid, fluorine, chlorine triflouride, or oxygen diflouride.

Hazardous decomposition products: Heavy Smoke, CO, CO₂, and irritating or toxic vapors and gases.

Section 11 - Toxicological Information

No toxicological test data is available for this product as manufactured. This product does contain crystalline silica. Repeated and prolonged exposures to dust containing crystalline silica can cause silicosis, cancer and autoimmune diseases.

Section 12 – Ecological Information

No ecotoxicity test data is available for this product. This product is not expected to present a hazard to aquatic and terrestrial environments.

Section 13 – Disposal Considerations

As supplied this product is non-hazardous. Consult federal, state and local regulations for proper disposal.

Section 14 – Transport Information

DOT Transportation Data (49 CFR 172.101):

Shipping Name: Not Regulated Packing Group: Not Determined

Shipping Symbols: N/A Label: Not Required

Hazard Class: Not Hazardous Special Provisions (172.102): None

ID No.: N/A

Date of Preparation: 2/16/2016

Section 15 – Regulatory Information

TSCA Inventory: All ingredients are on the TSCA inventory.

SARA Section 313: None above de minimus quantity.

SARA 311/312: None as supplied.

OSHA Hazardous Communication Categories: Dust is combustible and an irritant. Dust containing respirable crystalline silica is considered hazardous under the OSHA Hazardous Communication Standard.

Canada-WHMIS Classification: Non-hazardous

California Proposition 65: WARNING: This product can expose you to chemicals including crystalline silica (airborne particles of respirable size), which is known to the State of California to cause cancer. For more information go to www.P65Warnings.ca.gov.

Section 16 – Other Information

Refer to NFPA 654, standard for the prevention of fire and dust explosion from the manufacturing, processing and handling of combustible particulate solids, for safe handling of dusts generated during processing.

N/D - Not Determined N/A - Not Applicable

Prepared By: Ronald W. Allison

Last Revision: 11.08.22

Disclaimer: While the information and recommendations set forth in the SDS are believed to be accurate as of the date of the SDS preparation, Creative Pultrusions, Inc. makes no representation or warranty, direct or indirect, regarding their accuracy or completeness nor do we assume any obligations to advise you of any modifications or corrections to or of such information and recommendations of which we may become aware from the date hereof. Recipients are advised to confirm as they may deem acceptable that the information and recommendations are current and applicable to meet their requirements. Since the conditions are methods of use of this product are beyond our control, Creative Pultrusions, Inc. disclaims any and all liability arising out of the use of this product or the information provided herewith.